



2010 (Gen 2) SabreLite™

Meet the design that set the lighting standard for industrial safety and fire rescue. Our 2010 LED combines a traditional task light design with high performance LED technology and safety certifications. The rugged, lightweight polymer body incorporates a twist on/off lens shroud allowing for easy operation and superior impact resistance. The result? Possibly the toughest flashlight available on the market today.

- Twist on/off activation
- Waterproof IPX7
- Lifetime Guarantee of Excellence
- 22-hour runtime
- 3 "C" Batteries (not included)
- Heavy-duty body clip
- Split ring and security lanyard



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 8.11" (20.6 cm) |
|---------------|-----------------|

MATERIALS

| | |
|--------------------------------|--------------------------------|
| Body | EXL |
| O-Ring | Ethylene Propylene |
| Lens | Polycarbonate (PC) |
| Shroud | ABS |
| Clip | ABS |
| Contact Spring Retainer | Stainless Steel / Brass Nickel |

COLORS

| | |
|---|--|
|  Black |  High Visibility Yellow |
|---|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|-------------------------|----------|
| Battery Size | C |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Volts | 4.5v |

WEIGHT

| | |
|---------------------------------|------------------|
| Weight With Batteries | 13.4 oz (380 gr) |
| Weight Without Batteries | 5.4 oz (153 gr) |
| Packaged Weight | 7.0 oz (198 gr) |

SWITCH

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
Twisting Lens Shroud
Switch Type sales@pelican.com • www.pelican.com
Light Modes On / Off






Document created on 05-10-21

CERTIFICATIONS

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEX ia
InMetro

OTHER

Submersible yes
Minimum Pack 1
Military yes
Package Code C

| FL1 STANDARD | HIGH |
|---|---------------|
|  | 161 LUMENS |
|  | 22h 0mins |
|  | 160m |
|  | 6398cd |
|  | IPX7 |

ACCESSORIES